Validation of Soil Moisture and Ocean Salinity (SMOS) Soil Moisture Over Watershed Networks in the U.S.

Thomas J. Jackson, *Fellow, IEEE*, Rajat Bindlish, *Senior Member, IEEE*, Michael H. Cosh, Tianjie Zhao, *Student Member, IEEE*, Patrick J. Starks, David D. Bosch, Mark Seyfried, Mary Susan Moran, *Senior Member, IEEE*, David C. Goodrich, Yann H. Kerr, *Senior Member, IEEE*, and Delphine Leroux

Abstract—Estimation of soil moisture at large scale has been performed using several satellite-based passive microwave sensors and a variety of retrieval methods over the past two decades. The most recent source of soil moisture is the European Space Agency Soil Moisture and Ocean Salinity (SMOS) mission. A thorough validation must be conducted to insure product quality that will, in turn, support the widespread utilization of the data. This is especially important since SMOS utilizes a new sensor technology and is the first passive L-band system in routine operation. In this paper, we contribute to the validation of SMOS using a set of four in situ soil moisture networks located in the U.S. These ground-based observations are combined with retrievals based on another satellite sensor, the Advanced Microwave Scanning Radiometer (AMSR-E). The watershed sites are highly reliable and address scaling with replicate sampling. Results of the validation analysis indicate that the SMOS soil moisture estimates are approaching the level of performance anticipated, based on comparisons with the in situ data and AMSR-E retrievals. The overall root-mean-square error of the SMOS soil moisture estimates is 0.043 $\mbox{m}^{3}/\mbox{m}^{3}$ for the watershed networks (ascending). There are bias issues at some sites that need to be addressed, as well as some outlier responses. Additional statistical metrics were also considered. Analyses indicated that active or recent

Manuscript received April 2, 2011; revised June 24, 2011 and August 4, 2011; accepted August 31, 2011. Date of publication October 21, 2011; date of current version April 18, 2012.

- T. J. Jackson, R. Bindlish, M. H. Cosh, and T. Zhao are with the Hydrology and Remote Sensing Laboratory, Agricultural Research Service, U.S. Department of Agriculture, Beltsville, MD 20705 USA (e-mail: tom.jackson@ars.usda.gov; rajat.bindlish@ars.usda.gov; michael.cosh@ars.usda.gov; tianjie.zhao@ars.usda.gov).
- P. J. Starks is with the Grazinglands Research Laboratory, Agricultural Research Service, U.S. Department of Agriculture, El Reno, OK 73036 USA (e-mail: patrick.starks@ars.usda.gov).
- D. D. Bosch is with the Southeast Watershed Research Center, Agricultural Research Service, U.S. Department of Agriculture, Tifton, GA 31793 USA (e-mail: david.bosch@ars.usda.gov).
- M. Seyfried is with the Northwest Watershed Research Center, Agricultural Research Service, U.S. Department of Agriculture, Boise, ID 83712 USA (e-mail: mark.seyfried@ars.usda.gov).
- M. S. Moran and D. C. Goodrich are with the Southwest Watershed Research Center, Agricultural Research Service, U.S. Department of Agriculture, Tucson, AZ 85719 USA (e-mail: susan.moran@ars.usda.gov; dave.goodrich@ars.usda.gov).
- Y. H. Kerr and D. Leroux are with Centre d'Etudes Spatiales de la BIOsphère (CESBIO), 31401 Toulouse, France (e-mail: yann.kerr@cesbio.cnes.fr; delphine.leroux@cesbio.cnes.fr).
- Color versions of one or more of the figures in this paper are available online at http://ieeexplore.ieee.org.

Digital Object Identifier 10.1109/TGRS.2011.2168533

rainfall can contribute to interpretation problems when assessing algorithm performance, which is related to the contributing depth of the satellite sensor. Using a precipitation flag can improve the performance. An investigation of the vegetation optical depth (tau) retrievals provided by the SMOS algorithm indicated that, for the watershed sites, these are not a reliable source of information about the vegetation canopy. The SMOS algorithms will continue to be refined as feedback from validation is evaluated, and it is expected that the SMOS estimates will improve.

Index Terms—Advanced Microwave Scanning Radiometer (AMSR-E), passive microwave, Soil Moisture and Ocean Salinity (SMOS), soil moisture, validation.

I. INTRODUCTION

THE EUROPEAN Space Agency (ESA) Soil Moisture and Ocean Salinity (SMOS) [1], [2] satellite utilizes technology and algorithm approaches for soil moisture retrieval that have not been employed on satellite platforms in the past. It is also the first satellite to use L-band for routine measurements (a very limited effort using a sensor on Skylab is the only precedent [3]). Validation is important for any satellite-based remote sensing product, and it is particularly significant considering the unique features of the SMOS mission. The SMOS retrieval algorithms were developed using a combination of theoretical knowledge and tower observations, which must be validated for the low-resolution satellite sensor. A variety of methodologies can be used for validation purposes, which include ground-based, satellite estimates, and model products. Here, we focus on ground-based observations supported by satellite estimates.

Validation has always been challenging for passive microwave remote sensing of soil moisture using ground-based observations because of the disparity in spatial support of the measurements provided by the satellite and *in situ* sensors. Ground-based measurements of soil moisture are made at localized points, typically 0.0025 m², whereas satellite sensors provide an integrated area value for a much larger spatial extent (~1200 km² for SMOS). Spatial variations in soil moisture that must be considered within these footprints occur at a variety of scales including the point scale (soil properties), over geographic units (land cover, soils, and topography), and as the result of rainfall events and climate. There are several approaches that can be used to estimate the ground-based soil moisture from point observations over the satellite footprint

that include temporal stability analysis and variations of spatial sampling, both of which are utilized here [4], [5].

Another formidable challenge to validation is providing continuous long-term observations, which will provide a range of soil moisture conditions and seasonal patterns. In most cases, this is accomplished using *in situ* instrumentation, often integrated into a meteorological network. These are typically sparse and may provide only a single observation in a satellite footprint. In addition, a robust validation should include a wide range of vegetation, soil, and climate conditions if the results are to be used globally. The analysis presented in this paper is only one component of the overall SMOS validation [6]. Other contributions to this effort include [7] and [8].

The approach that we have developed for validating satellite-based soil moisture products is to compare the retrievals to verified estimates derived from intensive ground-based observing networks. This is founded on a set of four watershed scale *in situ* soil moisture networks in the U.S. These provide multiple point samples within domains that approximate a SMOS footprint for watersheds in diverse climate/vegetation regions.

The *in situ* networks were established in 2002 to support the validation of the Advanced Microwave Scanning Radiometers (AMSRs) on the ADEOS-2 and Aqua satellites [9], [10]. The reliability and accuracy of these networks have been established through extensive studies [11]. Data from the networks have been used in several related investigations [12]–[14]. These investigations have resulted in a good understanding of the accuracy of the various AMSR-E products that are available. In this paper, we will use this experience (nine years) and current AMSR-E products to assess the SMOS products. As we will describe, the two products are not expected to be the same; however, we expect that SMOS should be moving to the same level of performance that AMSR-E provides at these sites.

Data from the watershed networks and the AMSR-E products will be compared to the SMOS soil moisture products to assess the performance of the SMOS retrieval approach. Analysis will cover a full annual cycle. The quality of the *in situ* and AMSR-E data being used and the range of conditions available from these sites should be a significant contribution to the overall assessment of the SMOS mission.

It is important to note that the SMOS algorithm is evolving. As knowledge is gained from validation studies such as the one presented here, the parameters and algorithm structure are reevaluated. Exploiting this feedback is one of the reasons why validation studies are conducted. Therefore, we expect that the SMOS products will continue to improve. The current study uses the data available at the time of our analyses, which represents several incremental improvements since launch. All data were reprocessed by Centre d'Etudes Spatiales de la BIOsphère using the most recent version of the algorithm (v.400).

II. METHODOLOGY AND APPROACH

A robust soil moisture validation requires high-quality estimates over a wide range of cover conditions for varied climate and geographic domains. SMOS will rely on the contributions from many investigators to achieve this objective [6].

For this paper, we will utilize two validation resources: a set of densely sampled *in situ* sites and validated soil moisture products from AMSR-E. Analyses will build on our previous studies with AMSR-E [11]. Each soil moisture data set will be compared to SMOS retrievals for the period of January 2010 to December 2010. A brief description of the validation resources is provided in the following sections.

A. Dense Watershed Networks

The dense watershed networks are located at experimental watersheds operated by the USDA Agricultural Research Service; Walnut Gulch (WG), AZ; Little Washita (LW), OK; Little River (LR), GA; and Reynolds Creek (RC), ID. Soil moisture measurements taken on an hourly basis at a depth of 5 cm have been made at these validation sites on a continuous basis since 2002. For comparison to satellites, the nearest hourly instantaneous measurement is used. Each network is located in a different climatic region of the U.S., and each provides estimates of the average soil moisture over an area approximately the size of a SMOS footprint. Soils in WG and LR are generally sandy loam, whereas LW and RC have more diverse soil textures ranging from loam to clay to sand. Supporting studies to establish the calibration and scaling of these networks have been conducted in previous field experiments [15]-[17]. It was determined during these previous studies that the in situ networks accurately represent the soil moisture in those domains with high accuracy ($< 0.01 \text{ m}^3/\text{m}^3$) when compared to a thermo-gravimetrically collected soil moisture from 0 to 5 cm. The network average is a weighted average based on the Thiessen polygon method, with standard deviations generally between 0.05 and 0.10 m³/m³. Only the stations which consistently provided data are used in this calculation. Table I summarizes some key features of the sites. Additional details can be found in [11]. These watersheds are characteristic of the surrounding domains.

All of the SMOS footprints within the watershed were averaged. A simple drop-in-bucket type of approach was used for the SMOS footprints. This approach was adopted because a single SMOS footprint may cover only part of the watershed. Moreover, single point/footprint observations are likely to have higher variability and noise. Similar approaches have been used in earlier studies.

B. AMSR-E

A recent study [11] utilized the watershed networks with AMSR-E data to validate four alternative soil moisture algorithms over a seven-year period. Two results from that study are relevant to SMOS validation. First, the comparison of four algorithms with the *in situ* data revealed a quite different behavior (bias, range, and accuracy). Most algorithms could meet accuracy requirements with some modification (the target accuracy for NASA (http://nsidc.org/data/amsr_validation/pdfs/Version_3_SDV_Plan.pdf) and the Japanese Aerospace Exploration Agency [9] was 0.06 m³/m³). Based upon the statistics and sites studied, the single channel algorithm (SCA) [18] was found to perform as well or better than the alternatives

Watershed	Size	Soil	Climate	Annual	Common	Topography	Land Use
	(km ²)	Moisture		Rainfall	Soil Types		
		Sites		(mm)			
Walnut	148	21	Semiarid	320	Sandy Loam	Rolling	Range
Gulch, AZ							
Little	610	16	Sub	750	Silt, Loam/	Rolling	Range/wheat
Washita,			humid		Sand*		
OK							
Little	334	29	Humid	1200	Sandy Loam	Flat	Row
River, GA							crop/forest
Reynolds	238	19	Semiarid	500	Loam/Sandy	Mountainous	Range
Creek, ID					Loam *		

TABLE I USDA ARS WATERSHED CHARACTERISTICS

*Soils are heterogeneous.

TABLE II

COMPARISON OF LONG- AND SHORT-TERM SCA PERFORMANCES WITH AMSR-E. THE LONG-TERM ANALYSIS COVERS THE PERIOD OF JUNE 2002 TO DECEMBER 2010. THE SHORT TERM COVERS THE PERIOD OF THE SMOS DATA SET USED IN THE ANALYSES (JANUARY 2010 TO DECEMBER 2010)

Watershad	Desiled	AMS Descend	2007-007-2000	AMSR-E Ascending 1330				
Watershed	Period	RMSE	Bias	RMSE	Bias			
Walnut Gulch,	Long Term	0.024	-0.011	0.027	-0.016			
AZ	Short Term	0.038	-0.029	0.030	-0.021			
Little Washita, OK	Long Term	0.052	-0.019	0.047	-0.018			
	Short Term	0.046	-0.029	0.048	-0.035			
Little River,	Long Term	0.051	0.035	0.038	0.018			
GA	Short Term	0.049	0.040	0.034	0.021			
Reynolds	Long Term	0.027	-0.014	0.029	-0.017			
Creek, ID	Short Term	0.041	-0.035	0.044	-0.039			
RMSE (Root mean square error) and Bias are in m ³ /m ³ .								

tested, and it will be used here for comparisons with SMOS. Table II summarizes the SCA statistics over the seven-year period, which will be referred to as the long-term analysis.

Second, at this stage of SMOS validation, there is some risk in reaching a conclusion with a short period of record. To illustrate this potential pitfall, the two primary performance metrics used for AMSR-E [bias and root-mean-square error (rmse)] were computed for an increasing period of record from the launch date. These results are shown in Fig. 1 (note that RC was not used here because only summer season data are considered reliable at that site). The plots in Fig. 1 show that, for the watersheds with more vegetation (LR and LW), the performance in the initial months was poor, but improved after approximately six months. This could be the result of several factors, including the range of conditions observed; however, the message is clear that validation should proceed cautiously at the outset. It does appear that the metrics reached their long-term values after six months.




Fig. 1. AMSR-E volumetric soil moisture (VSM) validation with increasing period of record for descending (d) passes. (a) Bias. (b) RMSE. The legend refers to Little Washita (LW), Little River (LR), and Walnut Gulch (WG).

In order to assess whether the available period of record for SMOS was representative in terms of soil moisture conditions and retrievals, we computed the AMSR-E SCA statistics for this same period. These are shown in Table II and are referred to as short term. A comparison of these short-term values with the long-term values indicates that the SCA algorithm is performing approximately the same for the two periods of record for all watersheds. For the LW and LR watersheds, the short- and long-term rmse and bias are similar, which leads us to conclude that the general conditions at these sites over the first year of SMOS observations are typical of the climatology for these regions. The rmse and bias are larger in the short term for WG and RC. The increases are not that large; however, they do indicate that there may be anomalous conditions during this short term that do not reflect the typical conditions at these

				`							
Watershed	Product			ending 060 cending 0		SMOS Descending 1800 AMSR-E Ascending 1330					
	Troduct	RMSE	Bias	R	N	RMSE	Bias	R	N		
Walnut	SMOS	0.038	0.003	0.809	128	0.034	0.004	0.762	145		
Gulch, AZ	AMSR-E	0.038	-0.029	0.472	247	0.030	-0.021	0.471	216		
Little Washita, OK	SMOS	0.042	0.002	0.773	130	0.044	-0.008	0.775	134		
	AMSR-E	0.046	-0.029	0.709	214	0.048	-0.035	0.790	244		
Little River, GA	SMOS	0.051	0.026	0.732	126	0.072	0.045	0.643	92		
	AMSR-E	0.049	0.040	0.631	224	0.034	0.021	0.792	243		
Reynolds Creek, ID	SMOS	0.039	-0.023	0.152	51	0.045	-0.016	0.136	42		
	AMSR-E	0.041	-0.035	0.172	74	0.044	-0.039	0.045	76		
	RMSE (Root mean square error) and Bias are in m ³ /m ³ .										

R=Linear correlation coefficient, N=Number of samples

TABLE III

COMPARISON OF SMOS AND AMSR-E SCA SOIL MOISTURE ALGORITHM PERFORMANCE
FOR THE WATERSHED NETWORKS (JANUARY 2010 TO DECEMBER 2010)

watersheds. This will be taken into account in our assessment of the SMOS soil moisture retrievals.

Soil moisture retrievals from AMSR-E cannot be compared directly with SMOS products for several reasons that will be discussed below. Each satellite product must be compared to the *in situ* observations independently. The overall performance of the SMOS retrieval approach is then compared to that of the AMSR-E SCA for the same period of time. As discussed below, we expect the SMOS performance should be better than the AMSR-E SCA results.

SMOS and Aqua (AMSR-E) have different orbits, and as a result, they may or may not pass over the watershed sites on the same day. They also have different overpass times: SMOS ascending 0600-descending 1800 and AMSR-E ascending 1330-descending 0130 local time. As a result, they will be observing surface conditions at different points on the diurnal cycle. If it happened that both satellites covered a watershed on the same day, the diurnal effect would still be a noise factor. The observation time may also have a significant impact on the performance of the soil moisture algorithm. In general, the basic equations that these, as well as most other, algorithms are founded on assume uniform soil moisture and soil/vegetation temperature in the contributing depth. We expect that these assumptions are more likely to be true in the hours near dawn when the profiles have had the most time to return to an equilibrium state from the previous day's fluxes [19]. Therefore, based upon this aspect of retrieval, we might expect that the SMOS ascending 0600 soil moisture would have a better performance than either of the AMSR-E SCA products.

Another difference between AMSR-E and SMOS is the frequency/wavelength. The SCA, as with most other AMSR-E soil moisture algorithms, uses the X-band channel (frequency is 10.65 GHz, and wavelength is 2.8 cm). The longer wavelength C-band channels are not used due to widespread radio frequency interference; in particular, over the U.S., SMOS provides L-band (frequency is 1.41 GHz, and wavelength is 21.2 cm). It is well known that the contributing depth [20] of

the soil increases with wavelength, which results in a more stable value of soil moisture over the diurnal cycle. In addition, the effects of vegetation (in particular attenuation) are less significant at longer wavelengths [21].

Based upon the aforementioned discussion of the differences between AMSR-E SCA and SMOS soil moisture retrievals, the assumption is that the SMOS soil moisture algorithm should perform better than AMSR-E SCA. As a result, we use the AMSR-E SCA product performance as a metric, minimum level, for the SMOS product.

III. RESULTS AND DISCUSSION

The SMOS summary statistics for each watershed are shown in Table III. This table also includes the equivalent AMSR-E SCA results. These results have been matched up nominally in time for the two periods of day (early morning and afternoon). The overall results support the following statements.

- 1) The SMOS rmse is equal to or better than the AMSR-E SCA values, with the exception of LR.
- 2) The overall SMOS rmse values are $0.043 \text{ m}^3/\text{m}^3$ (ascending) and $0.047 \text{ m}^3/\text{m}^3$ (descending), which are very close to meeting the mission target of $0.04 \text{ m}^3/\text{m}^3$. These compare to the AMSR-E SCA values of $0.044 \text{ m}^3/\text{m}^3$ (descending) and $0.038 \text{ m}^3/\text{m}^3$ (ascending), respectively.
- 3) The rmse values do not appear to be impacted by the time of day (morning or afternoon) values (with the exception of LR descending).
- 4) The bias values must be carefully interpreted; in some cases, they are informative on algorithm performance (i.e., LR), and in others, they are not (i.e., WG).
- 5) With the exception of RC, which has a short season and low soil moisture, the correlation of the SMOS and *in situ* soil moisture is very good and, in general, better than that observed for AMSR-E.

In the following sections, we will analyze the results on an individual watershed basis. For each watershed, we examined




Fig. 2. In situ VSM versus satellite-retrieved soil moisture. (a) WG. (b) LW. (c) LR. (d) RC. In situ VSM is the network average for the nearest hourly time step to the satellite overpass.

the plots of observed versus estimated soil moisture (Fig. 2) and temporal plots of these and other variables (Figs. 3 and 4). The additional variables included temperature, precipitation, and vegetation.

A. Watershed Results

Walnut Gulch, AZ: The watershed has a semiarid climate. The precipitation varies significantly, with two-thirds of the annual precipitation occurring in the form of high-intensity convective thunderstorms with limited areal extent. Sparse desert shrubs and grass are the primary vegetation. The soil moisture exhibits a small range due to the well-drained sandy soils and limited rainfall in this area. Fig. 2(a) shows the comparison between *in situ* and retrieved soil moisture. The statistical comparison (Table III) indicated that there was a good agreement

between the watershed observations and SMOS estimates with near-zero bias. For WG, both the SMOS and AMSR-E SCA soil moisture products satisfy the mission target accuracy presented earlier.

A closer examination of Fig. 2(a) revealed that, unlike the AMSR-E SCA, SMOS produces some large overestimates (both ascending and descending) and that the near-zero bias may be misleading in terms of performance. Without these points, there would likely be a small underestimation bias, and the overall pattern of *in situ* versus estimated would be very similar to the AMSR-E SCA. Since these points appear to be somewhat anomalous, we investigated possible causes for overestimation by SMOS and focused on the points in Fig. 2(a) that were furthest from the equal value line.

Radio frequency interference was eliminated as a reason because there was no apparent problem in this region of the U.S.




Fig. 3. Temporal plots of in situ VSM and SMOS soil moisture and antecedent precipitation (ascending only). (a) WG. (b) LW. (c) LR. (d) RC.

We then examined the temporal plots of observed and estimated soil moisture and other variables: temperature, precipitation, and vegetation (only the precipitation and vegetation plots are shown in Figs. 3 and 4, respectively).

Temperature comparisons included the 5-cm *in situ* from the *in situ* network and the European Centre for Medium-Range

Weather Forecasts (ECMWF) 0–7-cm soil temperature that is used by SMOS in the soil moisture retrieval algorithm (ver. 400). The two temperature products matched up very well for WG for the morning overpass times (as well as for all the other watersheds). Errors were slightly larger for the evening. As an example, the rmse for the ECMWF product was 2.3 °C,




Fig. 4. Temporal plots of SMOS tau, VWC, and soil moisture (ascending only). (a) WG. (b) LW. (c) LR. (d) RC. In situ VSM is the network average for the nearest hourly time step to the satellite overpass.

with a bias of 1.8 °C. There was no apparent relationship between days with larger soil moisture errors and temperature. Note that an overestimation bias for temperature could lead to overestimation of soil moisture; however, the magnitude that

we observed here was very small, and as a result, we do not believe that temperature error plays a significant role in the soil moisture errors. This same observation was true for all the watersheds, and it will not be discussed any further.

TABLE IV
EFFECT OF FLAGGING AND REMOVAL ON SMOS SOIL MOISTURE ALGORITHM PERFORMANCE WHEN THERE IS ACTIVE OR RECENT RAINFALL

W 4 1 1	El	SN	MOS Asce	ending 060	00	SMOS Descending 1800				
Watershed	Flag	RMSE	Bias	R	N	RMSE	Bias	R	N	
Walnut	None	0.038	0.003	0.809	128	0.034	0.004	0.762	145	
	ECMWF	0.027	0.007	0.763	109	0.019	0.006	0.847	106	
Gulch, AZ	Active Rain	0.034	0.001	0.820	121	0.021	0.006	0.808	111	
	6-Hour Antecedent	0.024	0.008	0.678	106	0.019	0.007	0.840	100	
	None	0.042	0.002	0.773	130	0.044	-0.008	0.775	134	
Little	ECMWF	0.033	0.003	0.805	94	0.042	0.011	0.796	100	
Washita, OK	Active Rain	0.036	0.003	0.785	121	0.041	0.012	0.792	123	
	6-Hour Antecedent	0.036	0.003	0.780	112	0.042	0.013	0.767	115	
	None	0.051	0.026	0.732	126	0.072	0.045	0.643	92	
Little River,	ECMWF	0.054	-0.023	0.644	98	0.083	-0.059	0.610	87	
GA	Active Rain	0.049	-0.024	0.694	112	0.066	-0.038	0.653	77	
	6-Hour Antecedent	0.048	-0.024	0.717	96	0.064	-0.036	0.638	64	
	None	0.039	-0.023	0.152	51	0.045	-0.016	0.136	42	
Reynolds	ECMWF	0.038	0.026	0.230	48	0.039	0.025	0.129	36	
Creek, ID	Active Rain	0.040	0.025	0.083	47	0.039	0.027	0.342	37	
	6-Hour Antecedent	0.039	0.027	0.145	46	0.040	0.027	0.176	35	
	RMSE (Root mean square error) and Bias are in m³/m³. R=Linear correlation coefficient, N=Number of samples									

Another potential source of error in retrieval may be associated with the use of ECMWF soil moisture as the initial estimate in the iterative solution procedure used by SMOS. The ECMWF soil moisture products tend to overestimate soil moisture. It is possible that starting the iteration with soil moisture value that is too high might potentially bias the retrieval. However, in tests using the SMOS algorithm and initial estimates of 0 or 0.6 m³/m³, the same results were obtained. Using ECMWF soil moisture just saves some computation time by reducing the number of iterations and does not contribute to

the retrieval error.

As noted previously, precipitation in the WG region can be very intense and exhibit high spatial variability. Therefore, it is possible that the *in situ* network might not capture this variability, which is spatially integrated by the radiometer. For WG, as well as the other watersheds, we examined temporal plots of antecedent precipitation, as measured by rain gauges within the watershed, along with the *in situ* and SMOS estimated soil moisture (Fig. 3). Overestimation of soil moisture appears to be correlated with antecedent or possibly ongoing precipitation. The reason why there might be such a relationship is that the SMOS and the *in situ* measurements depths are very likely to be different during and shortly after a rain event. The depth of soil that contributes to the radiometer observation becomes shallow when the near surface is wet. This may occur during

and shortly after a precipitation event. After some elapsed time, the soil moisture profile will become more uniform. The in situ observations are centered at 5 cm and include a surrounding volume. Thus, it is likely that the SMOS estimate of soil moisture will be higher than the in situ when it is raining. This is not actually an error in the soil moisture algorithm; it is an error in the operational assumption that we make that the satellite sensor measures a certain depth on average. This cannot be corrected; however, it may be possible to flag such conditions. We examined this by using three different precipitation flags: the ECMWF forecast rainfall, the rain gauge data for a period of ± 0.5 h of the over pass (active precipitation), and the rain gauge data for the 6-h antecedent period. Using the occurrence of rainfall as detected by these flags, we filtered these retrievals from the statistical analyses of rmse and bias. The results are summarized in Table IV. Comparing these filtered data sets to the original for WG, we found a reduction in the rmse (for both ascending and descending) when using any of the flags. We also examined longer antecedent intervals, not presented here, and found that there was no further improvement in the rmse for WG or any of the other watersheds. Changes in the bias were very small. It was observed that the improvements offered by using either the ECMWF or active precipitation flag were larger for the evening overpasses (descending). This is attributed to the typically late afternoon, high intensity, and short duration rainfall in this region. These same factors may explain why the longer duration antecedent flag improves the morning (ascending) retrievals. It should be noted that the changes in rmse for the other watersheds were minor.

Overestimation following rainfall events is not evident in the AMSR-E SCA data shown in Fig. 2(a). The explanation for this may lie in the quality and implementation of rainfall flags of the SMOS and AMSR-E SCA retrieval algorithms. For AMSR-E SCA, a detection algorithm is used, which employs the higher frequency channels available and which provides information on current conditions. SMOS retrievals do not directly use the ECMWF precipitation to flag the estimated soil moisture. The ECMWF precipitation flag is used only in the case of heavy convective rainfall as an indicator of possible high canopy interception. The algorithm uses tau retrievals in subsequent orbits if there is no sufficient number of incidence angles available. The tau retrieval from the previous overpass is also used as a first guess in the iteration process. If there is a high canopy interception flag, then that tau is not used in the future retrievals.

It is possible that the number and intensity of precipitation events in 2010 were higher than normal. As noted earlier, the AMSR-E short-term statistics indicated that the errors were higher than usual in 2010. From this, we can infer that the performance statistics for SMOS in WG will likely improve as the period of record increases.

Another factor that we investigated was vegetation. Normalized Difference Vegetation Index (NDVI) climatology was derived using ten years (2000–2010) of MODIS (Terra) observations. Individual MODIS observations were screened for precipitation, cloud cover, and snow. Quality control flags were used to screen out bad data values. These quality controlled data were averaged for every 10-day period to derive a yearly climatology. The NDVI was converted to vegetation water content (VWC) using relationships established by comparing ground-based spectral observations with VWC observations obtained by destructive sampling. The following studies provide detailed descriptions of the methodology and the results based on several field campaigns [22]–[24].

The VWC data were used to analyze the vegetation optical depth or tau values [21] retrieved by the SMOS algorithm. Fig. 4(a) shows the plots for the ascending overpass (a similar behavior was observed for the descending passes, and summary values for both passes are included in Table VI). As noted previously, there is very little vegetation in WG. The changes that occur during the year are associated with rainfall events, which are more common during the late summer period. The VWC curve in Fig. 4(a) reflects these phenomena.

In Fig. 4(a), SMOS tau exhibits a large day-to-day variability that does not appear to be associated with actual changes in the vegetation. In addition, these deviations do not seem to be directly related to differences between the *in situ* and SMOS soil moisture since they occur during periods with both nominal as well as large errors and show no seasonal pattern. As described in [21], tau can be approximated by the product of VWC and a vegetation canopy parameter *b*. Using the guidelines for estimating *b* in [21], the resulting values of VWC for WG would be much higher than that observed in this area [22].

This result raises concerns on what the SMOS tau parameter is representing.

The variability of SMOS tau from day to day, the lack of a seasonal response, and the level of SMOS tau for this particular watershed indicated to us that these estimates may be dependent on other factors beyond the vegetation. These could include the quality of the brightness temperatures.

There are some issues with the SMOS field of view (FOV) that impact brightness temperature estimates at certain angles on some days. The fact that SMOS uses 2-D aperture synthesis results in snapshot images that include areas that are either in the alias-free or extended alias-free FOV. The extended zones have some sky present in the FOV. Only the center part of the snapshot contains the alias-free FOV. The edges of the orbit swath include observations from the extended alias-free FOV. Therefore, some of the variation in SMOS tau that we observed in Fig. 4(a) may be related to brightness temperature variations associated with this issue. Additional details on aliasing can be found in [25]–[28].

Little Washita, OK: The watershed has a subhumid climate. Soils include a wide range of textures with large regions of both coarse and fine textures. Land use is dominated by rangeland and pasture, with significant areas of winter wheat. The statistical comparison of *in situ* versus retrieved soil moisture (Table III) indicated that there was a good agreement; the SMOS rmse is a bit larger than the target accuracy but better than the AMSR-E SCA for both overpass times. The bias for SMOS was near zero, whereas the AMSR-E SCA had a moderate underestimation error.

Fig. 2(b) shows *in situ* versus retrieved soil moisture for SMOS and AMSR-E SCA. The overall patterns are similar to each other, but there were more overestimates for SMOS. Based upon these results, we believe that the SMOS algorithm is performing as expected for LW. It should be noted that the range of soil moisture for LW was one of the largest that we observed for the watershed sites.

As in the case of WG, we examined temporal plots of antecedent precipitation with the *in situ* and SMOS estimated soil moisture for LW (Fig. 3(b), ascending) and found some evidence of the pattern that we observed for WG. However, when the rmse values for the two precipitation flags were computed (Table IV), the impact of removing these events was smaller (a decrease from 0.042 to 0.036 m³/m³). The active and 6-h flags produced similar results, and bias was small for all cases. The use of precipitation improved the AMSR-E SCA by only a small amount.

The SMOS tau and VWC values for LW are presented as a temporal plot in Fig. 4(b) and are summarized in Table VI. The typical vegetation phenology for this region is clearly illustrated in the VWC. Winter wheat greens up in April and is harvested by early June. At the same time that the wheat is senescing, grasses and summer crops begin to contribute to the average VWC, which results in more or less constant VWC through summer. As observed for WG, SMOS tau does not exhibit any clear seasonal pattern, it has a high day-to-day variability, and the level of SMOS tau appears to be higher than expected.

Little River, GA: This watershed has a subhumid climate, with long hot and humid summers and short mild winters.

TABLE V
EFFECT OF FLAGGING AND REMOVAL ON AMSR-E SCA SOIL MOISTURE ALGORITHM PERFORMANCE WHEN THERE IS ACTIVE OR RECENT RAINFALL

XX7-411	E1	AMS	R-E Desce	ending 01.	30	AMSR-E Ascending 1330				
Watershed	Flag	RMSE	Bias	R	N	RMSE	Bias	R	N	
	None	0.038	-0.029	0.472	247	0.030	-0.021	0.471	216	
Walnut Gulch, AZ	Active Rain	0.028	-0.020	0.483	202	0.035	-0.026	0.388	205	
	6-Hour Antecedent	0.025	-0.018	0.364	170	0.032	-0.024	0.255	177	
	None	0.046	-0.029	0.709	214	0.048	-0.035	0.790	244	
Little Washita,	Active Rain	0.045	-0.029	0.702	208	0.045	-0.033	0.798	223	
OK	6-Hour Antecedent	0.045	-0.029	0.696	194	0.044	-0.033	0.790	207	
	None	0.049	0.040	0.631	224	0.034	0.021	0.792	243	
Little River, GA	Active Rain	0.048	0.039	0.609	208	0.034	0.023	0.784	205	
GA	6-Hour Antecedent	0.048	0.039	0.580	173	0.034	0.024	0.773	158	
	None	0.041	-0.035	0.172	74	0.044	-0.039	0.045	76	
Reynolds Creek, ID	Active Rain	0.039	-0.034	0.199	70	0.044	-0.039	0.080	69	
	6-Hour Antecedent	0.040	-0.035	0.118	59	0.042	-0.037	0.107	63	
	RMSE (Root mean square error) and Bias are in m ³ /m ³ . R=Linear correlation coefficient, N=Number of samples									

Sandy loam soils dominate. The major land cover in the watershed is cropland (consisting mostly of summer crops such as peanuts and cotton), forest, and pasture. The statistical comparisons in Table III indicate a higher rmse and an overestimation bias for SMOS ascending than that found for the other watersheds. This compares to good performance for the AMSR-E SCA algorithm, which also had an overestimation bias. Unlike the results for the other watersheds, there was a large increase in rmse and bias for the descending pass retrievals.

Fig. 2(c) further shows the aforementioned comments. It shows that the overall scatter of the *in situ* versus retrieved soil moisture is similar for SMOS and the AMSR-E SCA with one exception: SMOS has a large number of overestimates for the descending pass. We have previously suggested that one cause of these overestimation errors might be antecedent precipitation. Afternoon (evening) overpasses for SMOS (descending) occur during the time of day when convective rainfall is more likely to occur.

Fig. 3(c) shows the LR temporal plots of antecedent precipitation with the *in situ* and SMOS estimated soil moisture (ascending). The rmse and bias values for the two flags are summarized in Table IV. For the ascending passes, there is very little impact of using the flags, as indicated by the rmse. However, there was a change in the bias from overestimation to underestimation. For the descending passes, there is a small improvement (0.072 to $0.064 \, \mathrm{m}^3/\mathrm{m}^3$ when using the 6-h flag). These results suggest that some of the larger than expected error for LR may be associated with precipitation.

The LR SMOS tau values [Fig. 4(c)] exhibit the same day-today variability that we observed for the other watersheds. They also do not reflect the expected seasonal pattern that we would expect for this region based on VWC.

Reynolds Creek, ID: The land cover in the RC watershed is predominantly rangeland. About 75% of the annual precipitation in the higher elevations is snow, whereas less than 25% is snow at lower elevations. Soils range from steep rocky shallow soils in the mid elevations to rock-free saline soils in the valley to slightly acid soils in the upper elevations. In order to eliminate the effect of snow on SMOS retrievals, only the data from July–September were used in the analysis (this is the same approach used with the AMSR-E SCA). In reviewing Table III, we found, for RC, that the SMOS retrievals performed better than the AMSR-E SCA for the ascending passes and exceeded the target accuracy. There was an underestimation bias for both the ascending and descending data, and the descending value exceeds the target accuracy. Fig. 2(d) shows that the available data cover only a limited range of soil moisture conditions.

With regard to precipitation effects, there were few data points and even fewer precipitation events during the study period [Fig. 3(d)]. The precipitation flag results in Tables IV and V indicated that the use of the flags did not have much impact on rmse or bias.

The behavior of the RC SMOS tau values was different than what we observed for the other watersheds [Fig. 4(d)]. The day-to-day variations are present; however, there may be a pattern. There appears to be a cycle approximately every two weeks in which there is a rapid increase followed by a slower decay with a secondary increase. In addition, the increases in SMOS tau seem to correspond to increases in SMOS soil moisture (that is not explained by the *in situ* soil moisture). This result suggests

a problem related to the algorithm and may be associated with the orbit pattern and position of the site within the snapshot.

The general underestimation of soil moisture at this site [Fig. 3(d)] may be more apparent due to the overall drier conditions that typically occur. This could be associated with the choice of the soil dielectric mixing model, which might be re-evaluated in the future.

B. Discussion of Precipitation Flags

It is well known from theory [29] that both the amount of soil moisture and its distribution within the contributing depth of the soil can affect the resulting brightness temperature. With a complete radiative transfer model and a detailed description of the soil moisture (dielectric constant) profile, it is possible to simulate brightness temperature. However, it is not possible to retrieve the near-surface soil moisture profile from observations of brightness temperature, especially when the near-surface layer is wet. As a result, most retrieval algorithms incorporate the assumption of uniform soil moisture over a fixed depth (5 cm for L-band), which facilitates the use of the Fresnel equations in retrieval algorithms.

The *in situ* sensors are installed at a fixed depth in the watershed networks. Supplemental investigations were conducted to establish the relationship of these measurements and the soil moisture in the 0–5-cm layer. As a result, validation compares this verified average value to the radiometer estimate under the assumption that both sensors are responding to soil moisture within the same soil layer.

When rain occurs, it wets the layer from the surface. If the rain amount is large enough, a thin saturated soil layer can result in a contributing depth that is shallower than 5 cm. In this situation, the retrieved soil moisture may be accurate, but it is representative of a different depth than the *in situ* validation measurement. This will result in overestimation. The occurrence of this condition is more likely when the soil is initially dry and the precipitation event is of short duration and high intensity. We might expect this to be more significant for WG than the other watersheds, which supports the results in Table IV.

Following a rainfall event, the soil moisture within the surface soil layer will equilibrate through drainage and hydraulic redistribution. The time required to reach this state depends on the antecedent conditions, the intensity of precipitation, and the soil hydraulic properties.

The aforementioned discussion is meant to provide background on why SMOS soil moisture retrievals during active or after recent rainfall contribute to possible increased rmse and overestimation bias. Questions to consider are whether these retrievals should be included in validation and how these might be identified (flagged). We feel that the validation should be conducted with and without them, and both results should be presented. Based on our analyses, the ECMWF flag appears to perform about the same as those based on measured precipitation. Since these data are available to the SMOS retrieval algorithm, it is suggested that it should be implemented as a flag.

C. Discussion of Vegetation Optical Depth (Tau)

An intriguing aspect of the SMOS observations over land is the possibility of obtaining vegetation information from the tau or optical depth values provided as part of SMOS soil moisture retrieval. Tau is related to VWC and vegetation structure [18]. VWC is also related to vegetation indices such as the NDVI [22]–[24].

SMOS Tau is obtained by optimizing the brightness temperature observations within the algorithm approach [2]. The first guess is either derived from the previous acquisition (and then constrained using the brightness temperature observations) or from a leaf area index (LAI) climatology (not constrained). It is possible that the estimate from the LAI climatology can be significantly different from the SMOS estimated values of tau. These differences may explain some of the variations in the retrieved values. In the center part of the swath, a multiparameter retrieval is done [30]. If the pixel is located closer to the edge of the orbit, a smaller number of incidence angle observations will be available. In this case, the tau estimate from the previous acquisition is used in the soil moisture retrieval.

It is expected that tau does not vary on a daily basis. It is dependent on the vegetation phenology and follows a yearly cycle based on the vegetation growth. Significant variations are more likely to occur over a weekly time frame. SMOS has a revisit frequency of three days. However, only the center portion of the orbit has a sufficient number of incidence angles for the multiparameter retrieval. This results in an updated (retrieved) SMOS tau only every 7–10 days.

For the sites analyzed, we found that SMOS tau varied significantly on a day-to-day basis over the course of the year. This variability was not reflected in the soil moisture retrievals, with the exception of RC. Since we know that tau plays a significant role in attenuating the information from the soil, it is confusing that the variation in SMOS tau is not translated into variations in soil moisture. We can only conjecture that some other parameters in the algorithm are compensating for these changes.

None of the watershed sites had an annual pattern of SMOS tau that followed the typical seasonal pattern that we expect based upon the local climatology and VWC. We recognize that the analysis involves a limited set of conditions; however, the lack of a seasonal cycle in SMOS tau suggests that this parameter, as retrieved by the SMOS algorithm, is not a reliable indicator of VWC or biomass.

Another concern that we have with the SMOS tau as a vegetation indicator is the lack of its correspondence to the relative vegetation levels in the four watersheds. As shown in Table VI and as discussed in this paper, the SMOS tau levels are higher than expected. It is possible the higher SMOS tau values are a result of compensation for another model parameter. One such factor is the surface roughness effect. The effective roughness parameter was assumed to be a constant value of 0.1. Surface roughness and tau have a similar effect on the surface emissivity. It is possible the residual surface roughness is compensated by the increase in tau. The values for SMOS vegetation optical depth (tau) are significantly higher than the MODIS-derived tau for the WG and RC watersheds. These

					MODIC	. 137		MOI	NIC E .	1.00
Watershed	Overpass	SMOS Tau				estimated Vo Content (k		MODIS Estimated Tau		
Traversite a	o (espass	Average	Minimum	Maximum	Average	Minimum	Maximum	Average	Minimum	Maximum
Walnut	Ascending	0.18	0.01	0.42	0.59	0.40	0.00	0.059	0.048	0.090
Gulch, AZ	Descending	0.21	0.03	0.43		0.48	0.90			
Little	Ascending	0.24	0.06	0.43	1.17	0.79	1.40	0.117	0.079	0.140
Washita, OK	Descending	0.19	0.01	0.37			1.48			0.148
Little River,	Ascending	0.32	0.07	0.58	1.40	1.21	1.00	0.149	0.121	0.188
GA	Descending	0.30	0.07	0.57	1.49		1.88			
Reynolds Creek, ID	Ascending	0.22	0.08	0.43	0.77	0.69	0.94	0.077	0.069	0.094

TABLE VI
COMPARISON OF SMOS TAU AND VWC (DERIVED FROM NDVI CLIMATOLOGY VALUES).
PERIOD OF ANALYSIS IS JANUARY 2010 TO DECEMBER 2010

watersheds also have higher surface roughness. Based upon these facts, at the present time, the SMOS tau parameter should not be used as a vegetation index.

IV. SUMMARY

The results of our validation have indicated that the SMOS soil moisture estimates are approaching the level of performance anticipated, based on comparisons with *in situ* data and supported by soil moisture retrievals using AMSR-E data and its associated algorithm. The watershed sites are highly reliable and address scaling with replicate sampling. The overall rmse of the SMOS soil moisture estimates is $0.043~{\rm m}^3/{\rm m}^3$ (ascending) and $0.047~{\rm m}^3/{\rm m}^3$ (descending) for the watershed networks. These are very close to the mission target accuracy of $0.04~{\rm m}^3/{\rm m}^3$.

Our analyses have indicated that ongoing and recent precipitation can contribute to the error in using the *in situ* data to validate the SMOS retrievals. The *in situ* data represent average conditions in the 0–5-cm soil layer. At L-band, SMOS can also provide an estimate of this layer. However, shortly after a rain event, the radiometer measurement will be dominated by the wetter near-surface layer. The difference between the *in situ* and SMOS estimates of soil moisture in these cases is due to interpretation rather than retrieval error. It was shown that ECMWF precipitation forecast data can be used to flag these events. Applying this precipitation flag reduces the rmse in most cases.

SMOS provides a parameter tau as part of its retrieval scheme. Tau is the nadir vegetation optical depth and is related to the VWC and other biophysical variables. For the sites analyzed, we have found that SMOS tau varied significantly on a day-to-day basis, did not mimic the seasonal patterns that we expected for the sites, and did not match the level of tau as estimated using other techniques. Based upon these facts, the SMOS tau parameter should not be used as a vegetation index.

The SMOS algorithms are still being modified and are in calibration/validation phase. It is expected that refinements to the SMOS algorithm will further enhance the soil moisture retrievals.

ACKNOWLEDGMENT

The SMOS data were provided through the ESA supported SMOS Validation and Retrieval Team program.

The U.S. Department of Agriculture (USDA) prohibits discrimination in all its programs and activities on the basis of race, color, national origin, age, disability, applicability, sex, marital status, familial status, parental status, religion, sexual orientation, genetic information, political beliefs, and reprisal or because all or part of an individual's income is derived from any public assistance program (not all prohibited bases apply to all programs). Persons with disabilities who require alternative means for communication of program information (Braille, large print, audiotape, etc.) should contact USDA's TARGET Center at (202) 720-2600 (voice and TDD). To file a complaint of discrimination, write to USDA, Director, Office of Civil Rights, 1400 Independence Avenue, S.W., Washington, D.C. 20250-9410 USA, or call (800) 795-3272 (voice) or (202) 720-6382 (TDD). USDA is an equal opportunity provider and employer.

REFERENCES

- [1] Y. H. Kerr, P. Waldteufel, J. Wigneron, S. Delwart, F. Cabot, J. Boutin, M. Escorihuela, J. Font, N. Reul, C. Gruhier, S. E. Juglea, M. R. Drinkwater, A. Hahne, M. Martín-Neira, and S. Mecklenburg, "The SMOS mission: New tool for monitoring key elements of the global water cycle," *Proc. IEEE*, vol. 98, no. 5, pp. 666–687, May 2010.
- [2] Y. H. Kerr, P. Waldteufel, P. Richaume, J. P. Wigneron, P. Ferrazzoli, A. Mahmoodi, A. Al Bitar, F. Cabot, C. Gruhier, S. Juglea, D. Leroux, A. Mialon, and S. Delwart, "The SMOS soil moisture retrieval algorithm," *IEEE Trans. Geosci. Remote Sens.*, vol. 50, no. 5, pp. 1384–1403, May 2012
- [3] J. R. Eagleman and W. C. Lin, "Remote sensing of soil moisture by a 21-cm passive radiometer," *J. Geophys. Res.*, vol. 81, no. 21, pp. 3660– 3666, 1976.
- [4] L. Brocca, F. Melone, T. Moramarco, and R. Morbidelli, "Spatial-temporal variability of soil moisture and its estimation across scales," Water Resources Res., vol. 46, p. W02516, 2010. DOI:10.1029/2009WR008016.
- [5] A. W. Western and G. Bloschl, "On the spatial scaling of soil moisture," J. Hydrol., vol. 217, no. 3/4, pp. 203–224, Apr. 1999. DOI:10.1016/S0022-1694(98)00232-7.
- [6] S. Delwart, C. Bouzinac, P. Wursteisen, M. Berger, M. Drinkwater, M. Martín-Neira, and Y. H. Kerr, "SMOS validation and the COSMOS campaigns," *IEEE Trans. Geosci. Remote Sens.*, vol. 46, no. 3, pp. 695– 704, Mar. 2008.

- [7] A. Al Bitar, D. Leroux, Y. H. Kerr, O. Merlin, P. Richaume, A. Sahoo, and E. Wood, "Evaluation of SMOS soil moisture products over continental U.S. using the SCAN/SNOTEL network," *IEEE Trans. Geosci. Remote Sens.*, vol. 50, no. 5, pp. 1572–1586, May 2012
- [8] S. Peischl, J. P. Walker, C. Rüdiger, N. Ye, Y. H. Kerr, and E. Kim, "The AACES field experiments: SMOS calibration and validation across the Murrumbidgee River Catchment," *IEEE Trans. Geosci. Remote Sens.*, to be published.
- [9] A. Shibata, K. Imaoka, and T. Koike, "AMSR/AMSR-E level 2 and 3 algorithm developments and data validation plans of NASDA," *IEEE Trans. Geosci. Remote Sens.*, vol. 41, no. 2, pp. 195–203, Feb. 2003.
- [10] E. G. Njoku, T. J. Jackson, V. Lakshmi, T. K. Chan, and S. V. Nghiem, "Soil moisture retrieval from AMSR-E," *IEEE Trans. Geosci. Remote Sens.*, vol. 41, no. 2, pp. 215–229, Feb. 2003.
- [11] T. J. Jackson, M. Cosh, R. Bindlish, P. Starks, D. Bosch, M. Seyfried, D. Goodrich, S. Moran, and J. Du, "Validation of Advanced Microwave Scanning Radiometer soil moisture products," *IEEE Trans. Geosci. Remote Sens.*, vol. 48, no. 12, pp. 4256–4272, Dec. 2010.
- [12] Q. Liu, R. H. Reichle, R. Bindlish, M. H. Cosh, W. T. Crow, R. de Jeu, G. De Lannoy, G. J. Huffman, and T. J. Jackson, "The contributions of precipitation and soil moisture observations to the skill of soil moisture estimates in a land data assimilation system," *J. Hydrometeorol.*, vol. 12, no. 5, pp. 760–765, 2011.
- [13] D. Mirrales, W. T. Crow, and M. H. Cosh, "A technique for estimating spatial sampling errors in coarse-scale soil moisture estimates derived from point-scale observations," *J. Hydrometeorol.*, vol. 11, no. 6, pp. 1423–1429, 2010.
- [14] L. Li, P. W. Gaiser, B. C. Gao, R. M. Bevilacqua, T. J. Jackson, E. G. Njoku, C. Rüdiger, J. Calvet, and R. Bindlish, "WindSat global soil moisture retrieval and validation," *IEEE Trans. Geosci. Remote Sens.*, vol. 48, no. 5, pp. 2224–2241, May 2010.
- [15] M. H. Cosh, T. J. Jackson, P. J. Starks, and G. C. Heathman, "Temporal stability of surface soil moisture in the Little Washita and its applications in satellite soil moisture product validation," *J. Hydrol.*, vol. 323, no. 1–4, pp. 168–177, May 2006.
- [16] M. H. Cosh, T. J. Jackson, M. S. Moran, and R. Bindlish, "Temporal persistence and stability of surface soil moisture in a semi-arid watershed," *Remote Sens. Environ.*, vol. 112, pp. 304–313, 2008.
- [17] D. D. Bosch, V. Lakshmi, T. J. Jackson, M. Choi, and J. M. Jacobs, "Large scale measurements of soil moisture for validation of remotely sensed data: Georgia soil moisture experiment of 2003," *J. Hydrol.*, vol. 323, no. 1–4, pp. 120–137, May 2006.
- [18] T. J. Jackson, "Measuring surface soil moisture using passive microwave remote sensing," *Hydrol. Process.*, vol. 7, no. 2, pp. 139–152, Apr./Jun. 1993.
- [19] T. J. Jackson, "Profile soil moisture from surface measurements," J. Irrigation Drainage Div. ASCE, vol. 106, no. IR2, pp. 81–92, Jun. 1980.
- [20] F. T. Ulaby, R. K. Moore, and A. K. Fung, Microwave Remote Sensing, Active and Passive, Volume III: From Theory to Applications. Dedham, MA: Artech House, 1986.
- [21] T. J. Jackson and T. J. Schmugge, "Vegetation effects on the microwave emission from soils," *Remote Sens. Environ.*, vol. 36, no. 3, pp. 203–212, 1991.
- [22] M. T. Yilmaz, E. R. Hunt, Jr., L. D. Goins, S. L. Ustin, V. C. Vanderbilt, and T. J. Jackson, "Vegetation water content during SMEX04 from ground data and Landsat 5 Thematic Mapper imagery," *Remote Sens. Environ.*, vol. 112, no. 2, pp. 350–362, 2008.
- [23] T. J. Jackson, D. M. Le Vine, A. Y. Hsu, A. Oldak, P. J. Starks, C. T. Swift, J. D. Isham, and M. Haken, "Soil moisture mapping at regional scales using microwave radiometry: The Southern Great Plains hydrology experiment," *IEEE Trans. Geosci. Remote Sens.*, vol. 37, no. 5, pp. 2136–2151, Sep. 1999.
- [24] T. Jackson, D. Chen, M. Cosh, F. Li, M. Anderson, C. Walthall, P. Doraiswamy, and E. R. Hunt, "Vegetation water content mapping using Landsat data derived normalized difference water index (NDWI) for corn and soybean," *Remote Sens. Environ.*, vol. 92, no. 4, pp. 475–482, Sep. 2004.
- [25] E. Anterrieu, "A resolving matrix approach for synthetic aperture imaging radiometers," *IEEE Trans. Geosci. Remote Sens.*, vol. 42, no. 8, pp. 1649–1656, Aug. 2004.
- [26] E. Anterrieu, P. Waldteufel, and G. Caudal, "About the effects of instrument errors in interferometric radiometry," *Radio Sci.*, vol. 38, no. 3, p. 8044, 2003. DOI:10.1029/2002RS002750.
- [27] I. Corbella, F. Torres, A. Camps, A. Colliander, M. Martín-Neira, S. Ribó, K. Rautiainen, N. Duffo, and M. Vall-llossera, "MIRAS end-toend calibration: Application to SMOS L1 processor," *IEEE Trans. Geosci. Remote Sens.*, vol. 43, no. 5, pp. 1126–1134, May 2005.

- [28] A. Camps, M. Vall-llossera, N. Duffo, M. Zapata, I. Corbella, F. Torres, and V. Barrena, "Sun effects in 2D aperture synthesis radiometry imaging and their cancellation," *IEEE Trans. Geosci. Remote Sens.*, vol. 42, no. 6, pp. 1161–1167, Jun. 2004.
- [29] E. G. Njoku and J. A. Kong, "Theory for passive microwave remote sensing of near-surface soil moisture," *J. Geophys. Res.*, vol. 82, no. 20, pp. 3108–3118, 1977.
- [30] J. P. Wigneron, A. Chanzy, J. C. Calvet, and N. Bruguier, "A simple algorithm to retrieve soil moisture and vegetation biomass using passive microwave measurements over crop fields," *Remote Sens. Environ.*, vol. 51, no. 3, pp. 331–341, Mar. 1995.



Thomas J. Jackson (SM'96–F'02) received the Ph.D. degree from the University of Maryland, College Park, in 1976.

He is currently a Research Hydrologist with the Hydrology and Remote Sensing Laboratory, Agricultural Research Service, U.S. Department of Agriculture, Beltsville, MD. He is or has been a member of the science and validation teams of Aqua, ADEOS-II, RADARSAT, Oceansat-1, Envisat, ALOS, SMOS, Aquarius, GCOM-W, and SMAP remote sensing satellites. His research involves the

application and development of remote sensing technology in hydrology and agriculture, primarily microwave measurement of soil moisture.

Dr. Jackson is a Fellow of the Society of Photo-Optical Instrumentation Engineers, the American Meteorological Society, and the American Geophysical Union. In 2003, he received the William T. Pecora Award (NASA and Department of Interior) for outstanding contributions toward understanding the Earth by means of remote sensing and the AGU Hydrologic Sciences Award for outstanding contributions to the science of hydrology. He received the IEEE Geoscience and Remote Sensing Society Distinguished Achievement Award in 2011.



Rajat Bindlish (S'98–AM'99–M'03–SM'05) received the B.S. degree in civil engineering from the Indian Institute of Technology Bombay, Mumbai, India, in 1993 and the M.S. and Ph.D. degrees in civil engineering from The Pennsylvania State University, University Park, in 1996 and 2000, respectively.

He is currently with SSAI, working at the Hydrology and Remote Sensing Laboratory, Agricultural Research Service, U.S. Department of Agriculture, Beltsville, MD. His research interests involve the application of microwave remote sensing in hydrology.

He is currently working on soil moisture estimation from microwave sensors and their subsequent application in land surface hydrology.



stability.

Michael H. Cosh received the Ph.D. degree from Cornell University, Ithaca, NY, in 2002, when he joined the Agricultural Research Service (ARS).

He is currently a Research Hydrologist with the Hydrology and Remote Sensing Laboratory, ARS, U.S. Department of Agriculture, Beltsville, MD. His research involves the scaling of *in situ* ground data to remote sensing scales, spatial variability assessment of soil moisture, and developing methods to establish long-term validation sites for remote sensing platforms, including the use of temporal and spatial



Tianjie Zhao (S'09) received the B.S. degree from Beijing Normal University, Beijing, China, in 2007, where he is currently working toward the doctoral degree in cartography and geography information system.

He is also currently a Visiting Scientist with the Hydrology and Remote Sensing Laboratory, Agricultural Research Service, U.S. Department of Agriculture, Beltsville, MD. His research interests are microwave remote sensing of soil moisture and physical parameters of frozen soil.

Mr. Zhao received the scholarship award for excellent doctoral student granted by the Ministry of Education of China in 2011.



Patrick J. Starks received the B.S. degree in physical geography from the University of Central Arkansas, Conway, in 1979, the M.A. degree in physical geography from the University of Nebraska, Omaha, in 1984, and the Ph.D. degree in agronomy from the University of Nebraska, Lincoln, in 1990.

From 1990 to 1992, he was a Postdoctoral Fellow with the Department of Atmospheric Science, University of Missouri, Columbia. From 1992 to 1996, he was a Research Scientist with the National Agricultural Water Quality Laboratory, Agricultural Re-

search Service (ARS), U.S. Department of Agriculture (USDA), Durant, OK. Since 1996, he has been a Research Soil Scientist with the USDA-ARS Grazinglands Research Laboratory, El Reno, OK.



David D. Bosch received the Ph.D. degree in hydrology from The University of Arizona, Tucson, in 1990.

He joined the Agricultural Research Service (ARS), U.S. Department of Agriculture, in 1986. He is currently a Research Hydrologist with the Southeast Watershed Research Laboratory, ARS, Tifton, GA. He leads a watershed research program investigating the impacts of land use on water balance and quality. His primary research interests include watershed and landscape scale hydrology, agricultural

impacts on water quality, hydrologic and solute transport modeling of watershed processes, riparian buffer hydrology and solute transport, and developing new methods for assessing the impact of agricultural chemicals on ground and surface water supplies.

Dr. Bosch is a long-time member of the American Geophysical Union, the American Society of Agricultural and Biological Engineers, the American Society of Agronomy, and the Soil and Water Conservation Society.



Mark Seyfried received the Ph.D. degree in soil physics from the University of Florida, Gainesville, in 1986.

After postdoctoral research at the University of Delaware, Newark, he started working at the Agricultural Research Service, U.S. Department of Agriculture, Boise, ID, in 1988. Since then, much of his research has focused on using the plot-scale knowledge of soil and physics and plant physiology to the understanding of large watersheds. Although he has worked extensively in Florida, Delaware, New

Mexico, and Costa Rica, most of his work has been on the Reynolds Creek Experimental Watershed in Idaho. This has led to the publication of over 50 peer-reviewed manuscripts on topics of spatial variability and scaling, remote sensing, fire effects on ecohydrology, and streamflow generation processes. In addition, he has worked extensively on soil water measurement technology. His current research is on linking soil water and rangeland plant productivity at different scales, application of fiber optic cables for soil temperature monitoring, and linkage of remote sensing to plant productivity.

Dr. Seyfried is a long-time member of both the American Geophysical Union and the American Society of Agronomy.



Mary Susan Moran (SM'04) received the Ph.D. degree in soil and water science from the University of Arizona, Tucson, in 1990.

She is currently a Hydrologist with the Southwest Watershed Research Center, Agricultural Research Service, U.S. Department of Agriculture, Tucson. She also holds an adjunct faculty appointment with the Department of Soil, Water, and Environmental Science, The University of Arizona. She has also served on the NASA Landsat Science Team and EO-1 Validation Team to evaluate selected tech-

nologies for meeting soil science needs in the 21st century. Her research is concentrated on arid and semiarid regions, with a broad focus on the impact of global change on natural resource management and a specialized focus on the application of remote sensing to agricultural problems.

Dr. Moran is a member of the SMAP Science Definition Team and the Chair of the Applications Working Group.



David C. Goodrich received the Ph.D. degree in hydrology and water resources from The University of Arizona, Tucson, in 1990.

He has been a Research Hydraulic Engineer with the Southwest Watershed Research Center, Agricultural Research Service, U.S. Department of Agriculture, Tucson, since 1988. He Co-Led the interdisciplinary multiagency Semi-Arid Land-Surface-Atmosphere Research Program, and he is an Associate Adjunct Professor with the Department of Hydrology and Water Resources, The University

of Arizona. He is also an Executive Member of the NSF Sustainability of semi-Arid Hydrology and Riparian Areas Science and Technology Center as in charge of river systems research and has worked closely with policy and decision makers within the Upper San Pedro Partnership. His current research efforts are directed to scaling issues in watershed rainfall-runoff response, identification of dominant hydrologic processes over a range of basin scales, climatic change impacts on semiarid hydrologic response, incorporation of remotely sensed data into hydrologic models, functioning of semiarid riparian systems, and nonmarket valuation of ecosystem services.



Yann H. Kerr (M'88–SM'01) received the Engineering degree from the Ecole Nationale Supérieure de l'Aéronautique et de l'Espace (ENSAE), Toulouse, France, the M.Sc. degree in electronics and electrical engineering from the University of Glasgow, Glasgow, U.K., and the Ph.D. degree from Université Paul Sabatier, Toulouse.

From 1980 to 1985, he was employed by CNES. In 1985, he joined LERTS, for which he was the Director in 1993–1994. He spent 19 months at JPL,

Pasadena, CA, in 1987–1988. He has been with the Centre d'Etudes Spatiales de la Biosphère (CESBIO), Toulouse, since 1995 (Deputy Director and Director since 2007). In 1989, he started to work on the interferometric concept applied to passive microwave earth observation and was subsequently the Science Lead on the MIRAS project for ESA with MMS and OMP. He was also a Coinvestigator on IRIS, OSIRIS, and HYDROS for NASA. He was the Science Advisor for MIMR and Co I-on AMSR. He has been involved with many space missions. He is a member of the SMAP Science Definition Team. In 1997, he first proposed the natural outcome of the previous MIRAS work with what was to become the SMOS Mission to CNES, which was selected by ESA in 1999 with him as the SMOS mission Lead-Investigator and Chair of the Science Advisory Group. He is also in charge of the SMOS science activity coordination in France. He is currently involved in the exploitation of SMOS data, in the Cal Val activities and related level 2 soil moisture and levels 3 and 4 product development. He is also working on the SMOS next concept. His fields of interest are in the theory and techniques for microwave and thermal infrared remote sensing of the Earth, with emphasis on hydrology, water resources management, and vegetation monitoring.

Dr. Kerr has organized all the SMOS workshops, and he was a Guest Editor on three IEEE special issues.



Delphine Leroux received the Engineering degree in applied mathematics from the Institut National des Sciences Appliquées, Toulouse, France, in 2009. She has been working toward the Ph.D. degree at the Centre d'Etudes Spatiales de la Biosphère (CESBIO), Toulouse, since 2009.

She is currently working on the validation of SMOS data and on statistical methods to construct long and homogeneous time series of soil moisture.